

Customized Phase-adaptive Dimming Power Amplifier(Wall-mounted)

Model No: LTX0620L/LTX0620K/LTX0620D

Profile

- Dimming power amplifier adopt leading edge phase dimming
- Input 0/1-10V signal or KNX signal or DALI signal and convert into high power 0-220V TRIAC dimming.
- Applicable for incandescent lamps, dimmable LED lamps, and low-voltage halogen lamps with electronic transformer.
- Each channel output power up to 4000W.

Features


- Manual switch actuator/flickerless/relay off/multiple temperature protection /easy change channel card/built-in air switch
- Signal input buffer design, smooth dimming, timing \geq 220us
- Independent circuit breaker protection
- Manual switch and dimming
- Wall-mounted installation, convenient construction



Technical Parameters

Model No	LTX0620L	LTX0620K	LTX0620D
Brand	LAMMIN		
Input Signal	0/1-10V signal	KNX signal	DALI signal
Input Voltage	AC 380V		
Output Voltage	AC 0-220V		
Frequency Range	50/60Hz		
Max Load Current	20A/CH*6		
Max Output	4000W*6		
Min Load	60W		
Certification	CE		
Working Temp	-20°C~+50°C		
Warranty	3 years		
Size(L*W*H)MM	630*320*130		
Installation	Wall-mounted		
Customization	YES		

Wiring Diagram and Installations



- 1) Power Input AC380V(L3)
- 2) Power Input AC380V(L2)
- 3) Power Input AC380V(L1)
- 4) Zero line (N)
- 5) 6channel output
- 6) Input signal
- 7) PE Ground terminal
- 8) Manual switch
- 9) Led indicator